


650 VA – 3000 VA LINE INTERACTIVE UPS



*Product images may vary according to power values.

- Optional LED or LCD display
- Microprocessor based digital control
- Amplifier and reducer AVR for voltage stabilization
- Automatic frequency detection
- Wide input voltage range
- Power-On Security Test
- Cold Start
- Automatic restart when mains power is restored
- Mains phase tracking system to ensure that the inverter output voltage is in phase with the mains voltage

FEATURES AND VALUES



Maximum security
with CPU Control



Power with PFC
Factor Correction



Energy saving with
High Efficiency



Cold Start
(Battery Start)



Intelligent fan speed
changing according to load

SLDE 650 VA	390W
SLDE 800 VA	480W
SLDE 1200 VA	720W
SLDE 1500 VA	900W
SLDE 2000 VA	1200W
SLDE 3000 VA	1800W

You can access the product page by
scanning the QR Code with your phone.



- Intelligent battery management: battery temperature compensation to extend battery life; three-stage charging system to shorten charging time
- Short circuit, battery overcharge/over discharge, overload, surge voltage protection system
- Automatic charging in OFF mode
- Optional idle shutdown system
- Optional RS232 / USB communication port and RJ11 / RJ45 protection system
- Unattended security shutdown: System alarm and automatic Power On/Off system via RS232 or USB interface communicating with PC

MODEL		SLDE	SLDE	SLDE	SLDE	SLDE	SLDE
Strength		650 VA	800 VA	1200 VA	1500 VA	2000 VA	3000 VA
		390W	480W	720W	900W	1200W	1800W
Input							
Voltage	100 / 110 / 120 V: 80 ~ 150 Vac; 220 / 230 / 240 V: 162 ~ 295 Vac (145 ~ 295 Vac optional)						
Frequency	50 / 60 Hz ± 10% (auto-sensing)						
Output							
Voltage	100 / 110 / 120 Vac ± 10% or 220 / 230 / 240 Vac ± 10%						
Frequency	50 / 60 Hz ± 1% (auto-sensing)						
Waveform	Mains mode: pure sine wave; Battery mode: simulated sine wave						
Transfer Time	Typical 8 ms, 10 ms max.						
BATTERIES							
DC Voltage	12 V			24 V			48V
Configuration	12 V / 7.0 Ah × 1	12 V / 8.0 Ah × 1	12 V / 7.0 Ah × 2	12 V / 8.0 Ah × 2	12 V / 9.0 Ah × 2	12 V / 9.0 Ah × 4	
Charging Time	6 ~ 8 h						
OTHERS							
Protections	Short circuit - battery overcharge - overdischarge - overload - surge						
Communication	USB / RS232 (optional)						
No	20 ~ 90% RH @ 0 ~ 40°C (non-condensing)						
Noise Level	≤ 45 dB (1 m)						
Plastik Kasa	Net / Gross weight (kg)	4.3 / 4.6	5.2 / 5.5	8.6 / 9.0	10.1 / 10.5	/	
	Dimensions (W × D × H) (mm)	100 × 290 × 140		140 × 345 × 170		/	
	Packaged dimensions (W × D × H) (mm)	139 × 335 × 210		198 × 406 × 245		/	
	Quantity / 20 ft	2300 pcs		1000 pcs		/	
Metal Country	Net / Gross weight (kg)	5.1 / 5.4	6.3 / 6.6	9.6 / 10.1	11.3 / 11.7	12.9 / 13.3	19.3 / 20.6
	Dimensions (W × D × H) (mm)	95 × 320 × 160		125 × 320 × 225		125 × 380 × 225	157.5 × 452 × 211
	Packaged dimensions (W × D × H) (mm)	145 × 375 × 230		180 × 390 × 295		180 × 450 × 295	238 × 536 × 295
	Quantity / 20 ft	2000 pcs		1000 pcs		658 pcs	